

OpenStack Charm Deployment without Canonical MAAS for Testing & Small Deployment

Gusriandi

Cloud Development Engineer @Datacomm

<https://www.linkedin.com/in/randifilan/>



EasyStack
open cloud computing



flexi

WOWRACK



ZConverter Cloud



SIVALI
CLOUD
TECHNOLOGY

boer
technology

NASHTAGROUP

nevacloud

Yogyakarta, 19 July 2025



Introduction

- OpenStack Deployment Tools
- OpenStack Charm
- Juju
- Charm
- MAAS

Introduction

Juju, the orchestrator engine

Juju is an open source orchestration engine for software operators that enables the deployment, integration and lifecycle management of applications at any scale, on any infrastructure.


Charms, the software operators

A charm is an operator: business logic encapsulated in reusable software packages that automate every aspect of an application's life.


Charms are developed with the Charm SDK which comprises the:

- **Ops library:** a Python framework for developing and testing charms
- **Charmcraft:** a tool for building, packaging and publishing charms.

Typical Topology Deployment



Deployment Topology



Install & Configure LXD

- Install LXD on `oscm-con-01`

```
ubuntu@oscm-con-01:~$ sudo snap install lxd
2025-05-28T05:30:05Z INFO Waiting for automatic snapd restart...
lxd (5.21/stable) 5.21.3-c5ae129 from Canonical✓ installed
```

auto



- Install LXD on `oscm-cmp-01`

```
ubuntu@oscm-cmp-01:~$ sudo snap install lxd
2025-05-28T06:30:05Z INFO Waiting for automatic snapd restart...
lxd (5.21/stable) 5.21.3-c5ae129 from Canonical✓ installed
```

auto



- Install LXD on `oscm-cmp-02`

```
ubuntu@oscm-cmp-02:~$ sudo snap install lxd
2025-05-28T16:11:27Z INFO Waiting for automatic snapd restart...
lxd (5.21/stable) 5.21.3-c5ae129 from Canonical✓ installed
```

auto



Install & Configure LXD

- Configure LXD on `oscwm-con-01`, `oscwm-cmp-01`, `oscwm-cmp-02`

```
root@oscwm-con-01:/home/ubuntu# sudo lxd init --preseed <<EOF
config:
  core.https_address: '[:,]:8443'
networks: []
storage_pools:
- name: lvm
  driver: lvm
  config:
    source: /dev/vdd
profiles:
- name: default
  description: "Default LXD Network"
  config: {}
  devices:
    eth0:
      name: eth0
      nictype: bridged
      parent: os-external
      type: nic
    root:
      path: /
      pool: lvm
      type: disk
projects: []
cluster: null
EOF
root@oscwm-cmp-02:/home/ubuntu#
```

Install Juju & Bootstrap Controller

- Create LXC Container on `oscwm-con-01` for `juju-controller`

```
root@oscwm-con-01:/home/ubuntu# lxc launch ubuntu:22.04 juju-controller
```

```
Creating juju-controller
```

```
Starting juju-controller
```

```
root@oscwm-con-01:/home/ubuntu# lxc list
```

NAME	STATE	IPV4	IPV6	TYPE	SNAPSHOTS
juju-controller	RUNNING	10.210.121.254 (eth0)		CONTAINER	0

- Install Juju Client on LXC Container `juju-controller` in `oscwm-con-01`

```
ubuntu@oscwm-con-01:~$ sudo lxc exec juju-controller bash
```

```
root@juju-controller:~# su - ubuntu
```

```
ubuntu@juju-controller:~$ wget https://launchpad.net/juju/3.6/3.6.8/+download/juju-3.6.8-linux-amd64.tar.xz
```

```
ubuntu@juju-controller:~$ tar xf juju-3.6.8-linux-amd64.tar.xz
```

```
ubuntu@juju-controller:~$ sudo install -o root -g root -m 0755 juju /usr/local/bin/juju
```

Install Juju & Bootstrap Controller

- Configure SSH Config

```
ubuntu@juju-controller:~$ cat .ssh/config
Host oscwm-con-01
    Hostname 10.210.121.100
    User ubuntu
Host oscwm-cmp-01
    Hostname 10.210.121.101
    User ubuntu
Host oscwm-cmp-02
    Hostname 10.210.121.102
    User ubuntu
Host juju-controller
    Hostname 10.210.121.254
    User ubuntu
```

- Enable Passwordless SSH

```
ubuntu@juju-controller:~/.ssh$ ssh-keygen
ubuntu@juju-controller:~$ ssh-copy-id ubuntu@10.210.121.254 #juju-controller
ubuntu@juju-controller:~$ ssh-copy-id ubuntu@10.210.121.100 #oscwm-cmp-01
ubuntu@juju-controller:~$ ssh-copy-id ubuntu@10.210.121.101 #oscwm-cmp-01
ubuntu@juju-controller:~$ ssh-copy-id ubuntu@10.210.121.102 #oscwm-cmp-02
```

- Create Static Host

```
ubuntu@juju-controller:~$ cat /etc/hosts
10.210.121.254 juju-controller
10.210.121.100 oscwm-con-01
10.210.121.101 oscwm-cmp-01
10.210.121.102 oscwm-cmp-02
```

Install Juju & Bootstrap Controller

- Bootstrap Juju controller on `juju-controller` LXD Container

```
ubuntu@juju-controller:~$ juju bootstrap manual/juju-controller --bootstrap-series=jammy juju-controller
Creating Juju controller "juju-controller" on manual
Looking for packaged Juju agent version 3.6.8 for amd64
Located Juju agent version 3.6.8-ubuntu-amd64 at https://streams.canonical.com/juju/tools/agent/3.6.8/juju-3.6.8-linux-amd64.tgz
Installing Juju agent on bootstrap instance
Running machine configuration script...
Bootstrap agent now started
Contacting Juju controller at juju-controller to verify accessibility...

Bootstrap complete, controller "juju-controller" is now available
Controller machines are in the "controller" model

Now you can run
    juju add-model <model-name>
to create a new model to deploy workloads.
```

- Add Juju Model

```
ubuntu@juju-controller:~$ juju add-model --config default-series=jammy openstack-lab
Added 'openstack-lab' model with credential 'default' for user 'admin'
```



Add Machine to Juju & Network Space

Add Machine to Juju & Space

- Add machine `oscwm-con-01` , `oscwm-cmp-01` , `oscwm-cmp-02`

```
ubuntu@juju-controller:~$ juju add-machine ssh:ubuntu@oscwm-con-01 --private-key /home/ubuntu/.ssh/id_rsa
created machine 0
ubuntu@juju-controller:~$ juju add-machine ssh:ubuntu@oscwm-cmp-01 --private-key /home/ubuntu/.ssh/id_rsa
created machine 1
ubuntu@juju-controller:~$ juju add-machine ssh:ubuntu@oscwm-cmp-02 --private-key /home/ubuntu/.ssh/id_rsa
created machine 3
```

- List Machine

```
ubuntu@juju-controller:~$ juju machines
```

Machine	State	Address	Inst id	Base	AZ	Message
0	started	10.210.121.100	manual:oscwm-con-01	ubuntu@22.04		Manually provisioned machine
1	started	10.210.121.101	manual:oscwm-cmp-01	ubuntu@22.04		Manually provisioned machine
3	started	10.210.121.102	manual:oscwm-cmp-02	ubuntu@22.04		Manually provisioned machine

Add Machine to Juju & Space

- Default Space

```
ubuntu@juju-controller:~$ juju spaces
Name  Space ID  Subnets
alpha  0         10.210.121.0/24
      0         10.210.122.0/24
      0         10.210.140.0/24
      0         10.210.150.0/24
```

- Add spaces

```
ubuntu@juju-controller:~$ juju add-space external 10.210.121.0/24
added space "external" with subnets 10.210.121.0/24
ubuntu@juju-controller:~$ juju add-space internal 10.210.122.0/24
added space "internal" with subnets 10.210.122.0/24
ubuntu@juju-controller:~$ juju add-space storage 10.210.140.0/24
added space "storage" with subnets 10.210.140.0/24
ubuntu@juju-controller:~$ juju add-space overlay 10.210.150.0/24
added space "overlay" with subnets 10.210.150.0/24
```

```
ubuntu@juju-controller:~$ juju spaces
Name      Space ID  Subnets
alpha     0
external  1         10.210.121.0/24
internal  2         10.210.122.0/24
storage   3         10.210.140.0/24
overlay   4         10.210.150.0/24
```



Deploy Ceph, MySQL, RabbitMQ

Deploy Ceph Cluster

We will deploy `ceph-mon`, `ceph-osd` to machine `0`, `1`, `2`

- Deploy Ceph Cluster

```
ubuntu@juju-controller:~$ juju deploy -n 3 --to 0,1,2 --channel latest/edge --config openstack-lab.yaml ceph-osd os-ceph-osd
Deployed "os-ceph-osd" from charm-hub charm "ceph-osd", revision 632 in channel latest/edge on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy -n 3 --to 0,1,2 --channel latest/edge --config openstack-lab.yaml ceph-mon os-ceph-mon
Deployed "os-ceph-mon" from charm-hub charm "ceph-mon", revision 268 in channel latest/edge on ubuntu@22.04/stable
ubuntu@juju-controller:~$ juju integrate os-ceph-mon:osd os-ceph-osd:mon

ubuntu@juju-controller:~$ juju bind os-ceph-mon external admin=internal cluster=storage dashboard=external mds=storage metrics-endpoint=external mon=storage
osd=storage prometheus=external public=external client=storage
ubuntu@juju-controller:~$ juju bind os-ceph-osd external cluster=storage mon=storage nrpe=external-master=external public=external secrets-storage=external
```

Deploy Ceph Cluster

[ubuntu@juju-controller:~\$ juju status os-ceph-*

Model	Controller	Cloud/Region	Version	SLA	Timestamp
openstack-lab	juju-controller	manual	3.6.8	unsupported	13:28:00+07:00

App	Version	Status	Scale	Charm	Channel	Rev	Exposed	Message
os-ceph-mon	19.2.0	active	3	ceph-mon	latest/edge	268	no	Unit is ready and clustered
os-ceph-osd	19.2.0	active	3	ceph-osd	latest/edge	632	no	Unit is ready (1 OSD)
os-neutron-gateway	23.1.0	active	1	neutron-gateway	2024.1/stable	539	no	Unit is ready
os-neutron-openvswitch	23.1.0	active	0	neutron-openvswitch	2024.1/stable	578	no	Unit is ready
os-nova-compute	28.2.0	active	2	nova-compute	2024.1/stable	771	no	Unit is ready

Unit	Workload	Agent	Machine	Public address	Ports	Message
os-ceph-mon/0*	active	idle	0	10.210.121.100		Unit is ready and clustered
os-ceph-mon/1	active	idle	1	10.210.121.101		Unit is ready and clustered
os-ceph-mon/2	active	idle	2	10.210.121.102		Unit is ready and clustered
os-ceph-osd/0*	active	idle	0	10.210.121.100		Unit is ready (1 OSD)
os-ceph-osd/1	active	idle	1	10.210.121.101		Unit is ready (1 OSD)
os-ceph-osd/2	active	idle	2	10.210.121.102		Unit is ready (1 OSD)
os-neutron-gateway/0*	active	idle	0	10.210.121.100		Unit is ready
os-nova-compute/0*	active	idle	1	10.210.121.101		Unit is ready
os-neutron-openvswitch/1	active	idle		10.210.121.101		Unit is ready
os-nova-compute/1	active	idle	2	10.210.121.102		Unit is ready
os-neutron-openvswitch/0*	active	idle		10.210.121.102		Unit is ready

Machine	State	Address	Inst id	Base	AZ	Message
0	started	10.210.121.100	manual:oscwm-con-01	ubuntu@22.04		Manually provisioned machine
1	started	10.210.121.101	manual:oscwm-cmp-01	ubuntu@22.04		Manually provisioned machine
2	started	10.210.121.102	manual:oscwm-cmp-02	ubuntu@22.04		Manually provisioned machine

Deploy Ceph Cluster

```
[ubuntu@juju-controller:~$ juju ssh 0 sudo ceph -s
```

```
cluster:
```

```
  id:      f18e812e-6087-11f0-8c23-fd9831d73258
```

```
  health: HEALTH_OK
```

```
services:
```

```
  mon: 3 daemons, quorum oscwm-con-01,oscwm-cmp-01,oscwm-cmp-02 (age 46h)
```

```
  mgr: oscwm-cmp-02(active, since 46h), standbys: oscwm-cmp-01, oscwm-con-01
```

```
  osd: 3 osds: 3 up (since 46h), 3 in (since 46h)
```

```
data:
```

```
  pools:  4 pools, 49 pgs
```

```
  objects: 133 objects, 183 MiB
```

```
  usage:   447 MiB used, 300 GiB / 300 GiB avail
```

```
  pgs:     49 active+clean
```

```
Connection to 10.210.140.100 closed.
```

```
ubuntu@juju-controller:~$ |
```

Deploy MySQL InnoDB Cluster

We will deploy `mysql-innodb-clusters` to LXD on machine `0, 1, 2`

- Deploy mysql-innodb-clusters

auto

```
ubuntu@juju-controller:~$ juju deploy -n 3 --to lxd:0,lxd:1,lxd:2 --channel 8.0/stable --config openstack-lab.yaml mysql-innodb-cluster os-mysql-innodb-clusters
--constraints spaces=external,internal --bind "external cluster=internal coordinator=internal db-monitor=internal db-router=internal shared-db=internal"
Deployed "os-mysql-innodb-clusters" from charm-hub charm "mysql-innodb-cluster", revision 159 in channel 8.0/stable on ubuntu@22.04/stable
```

- Deploy in Progress

auto

```
ubuntu@juju-controller:~$ juju status
Model          Controller    Cloud/Region  Version  SLA          Timestamp
openstack-lab  juju-controller  manual        3.6.8    unsupported   22:05:38+07:00

App            Version  Status  Scale  Charm          Channel    Rev  Exposed  Message
os-mysql-innodb-clusters  waiting  0/3    mysql-innodb-cluster  8.0/stable  159  no       waiting for machine

Unit           Workload  Agent    Machine  Public address  Ports  Message
os-mysql-innodb-clusters/6  waiting  allocating  0/lxd/2                waiting for machine
os-mysql-innodb-clusters/7  waiting  allocating  1/lxd/2                waiting for machine
os-mysql-innodb-clusters/8  waiting  allocating  2/lxd/2                waiting for machine
```

Deploy MySQL InnoDB Cluster

```
[ubuntu@juju-controller:~]$ juju status os-mysql-innodb-clusters
Model          Controller    Cloud/Region  Version  SLA          Timestamp
openstack-lab  juju-controller  manual        3.6.8    unsupported   13:55:52+07:00

App            Version  Status  Scale  Charm          Channel  Rev  Exposed  Message
os-mysql-innodb-clusters  8.0.42  active    3  mysql-innodb-cluster  8.0/stable  159  no      Unit is ready: Mode: R/O, Cluster is ONLINE and can tolerate up to ONE failure.

Unit            Workload  Agent  Machine  Public address  Ports  Message
os-mysql-innodb-clusters/6  active  idle    0/lxd/2  10.210.121.242  Unit is ready: Mode: R/O, Cluster is ONLINE and can tolerate up to ONE failure.
os-mysql-innodb-clusters/7  active  idle    1/lxd/2  10.210.121.240  Unit is ready: Mode: R/O, Cluster is ONLINE and can tolerate up to ONE failure.
os-mysql-innodb-clusters/8* active  idle    2/lxd/2  10.210.121.241  Unit is ready: Mode: R/W, Cluster is ONLINE and can tolerate up to ONE failure.

Machine  State  Address          Inst id          Base             AZ  Message
0        started  10.210.121.100  manual:oscwm-con-01  ubuntu@22.04  Manually provisioned machine
0/lxd/2  started  10.210.121.242  juju-42d5f2-0-lxd-2  ubuntu@22.04  Container started
1        started  10.210.121.101  manual:oscwm-cmp-01  ubuntu@22.04  Manually provisioned machine
1/lxd/2  started  10.210.121.240  juju-42d5f2-1-lxd-2  ubuntu@22.04  Container started
2        started  10.210.121.102  manual:oscwm-cmp-02  ubuntu@22.04  Manually provisioned machine
2/lxd/2  started  10.210.121.241  juju-42d5f2-2-lxd-2  ubuntu@22.04  Container started
ubuntu@juju-controller:~$
```

Deploy RabbitMQ

We will deploy `rabbitmq-server` to LXD on machine `0`

auto ↕

```
ubuntu@juju-controller:~$ juju deploy -n 1 --to lxd:0 --channel 3.9/stable --config openstack-lab.yaml ch:rabbitmq-server os-rabbitmq-server --constraints spaces=external,internal --bind "external amqp=internal"

Deployed "os-rabbitmq-server" from charm-hub charm "rabbitmq-server", revision 246 in channel 3.9/stable on ubuntu@22.04/stable
```

[ubuntu@juju-controller:~\$ juju status os-rabbitmq-server

Model	Controller	Cloud/Region	Version	SLA	Timestamp
openstack-lab	juju-controller	manual	3.6.8	unsupported	13:58:49+07:00

App	Version	Status	Scale	Charm	Channel	Rev	Exposed	Message
os-rabbitmq-server	3.9.27	active	1	rabbitmq-server	3.9/stable	246	no	Unit is ready

Unit	Workload	Agent	Machine	Public address	Ports	Message
os-rabbitmq-server/0*	active	idle	0/lxd/3	10.210.121.239	5672,15672/tcp	Unit is ready

Machine	State	Address	Inst id	Base	AZ	Message
0	started	10.210.121.100	manual:oscm-con-01	ubuntu@22.04		Manually provisioned machine
0/lxd/3	started	10.210.121.239	juju-42d5f2-0-lxd-3	ubuntu@22.04		Container started

ubuntu@juju-controller:~\$ |



Deploy OpenStack Service

Deploy Keystone

We will deploy `keystone` to LXD on machine `0`

auto

```
ubuntu@juju-controller:~$ juju deploy -n 1 --to lxd:0 --channel 2024.1/stable --config openstack-lab.yaml ch:keystone os-keystone --constraints spaces=external,internal --bind "external cluster=internal ha=internal shared-db=internal"
Deployed "os-keystone" from charm-hub charm "keystone", revision 726 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy --channel 8.0/stable mysql-router os-keystone-mysql-router --bind "external shared-db=internal db-router=internal"
Deployed "os-keystone-mysql-router" from charm-hub charm "mysql-router", revision 201 in channel latest/edge on ubuntu@22.04/stable
ubuntu@juju-controller:~$ juju relate os-keystone-mysql-router:db-router os-mysql-innodb-clusters:db-router
ubuntu@juju-controller:~$ juju relate os-keystone-mysql-router:shared-db os-keystone:shared-db
```

[ubuntu@juju-controller:~\$ juju status os-keystone

Model	Controller	Cloud/Region	Version	SLA	Timestamp
openstack-lab	juju-controller	manual	3.6.8	unsupported	14:08:29+07:00

App	Version	Status	Scale	Charm	Channel	Rev	Exposed	Message
os-keystone	24.0.0	active	1	keystone	2024.1/stable	726	no	Application Ready
os-keystone-mysql-router	8.0.42	active	1	mysql-router	8.0/stable	257	no	Unit is ready

Unit	Workload	Agent	Machine	Public address	Ports	Message
os-keystone/1*	active	idle	0/lxd/5	10.210.121.237	5000/tcp	Unit is ready
os-keystone-mysql-router/1*	active	idle		10.210.121.237		Unit is ready

Machine	State	Address	Inst id	Base	AZ	Message
0	started	10.210.121.100	manual:oscwm-con-01	ubuntu@22.04		Manually provisioned machine
0/lxd/5	started	10.210.121.237	juju-42d5f2-0-lxd-5	ubuntu@22.04		Container started

Deploy Glance

We will deploy `glance` to machine `0`

```
ubuntu@juju-controller:~$ juju deploy -n 1 --to lxd:0 --channel 2024.1/stable --config openstack-lab.yaml ch:glance os-glance --constraints spaces=external,internal,storage --bind "external admin=internal amqp=internal ceph=storage cluster=internal ha=internal image-service=internal internal=internal shared-db=internal"
Deployed "os-glance" from charm-hub charm "glance", revision 621 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy --channel 8.0/stable mysql-router os-glance-mysql-router --bind "external shared-db=internal db-router=internal"
Deployed "os-glance-mysql-router" from charm-hub charm "mysql-router", revision 257 in channel 8.0/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju relate os-glance-mysql-router:db-router os-mysql-innodb-clusters:db-router
ubuntu@juju-controller:~$ juju relate os-glance-mysql-router:shared-db os-glance:shared-db
ubuntu@juju-controller:~$ juju relate os-glance:identity-service os-keystone:identity-service
ubuntu@juju-controller:~$ juju relate os-ceph-mon:client os-glance:ceph
```

`ubuntu@juju-controller:~$ juju status os-glance`

Model	Controller	Cloud/Region	Version	SLA	Timestamp
openstack-lab	juju-controller	manual	3.6.8	unsupported	14:07:13+07:00

App	Version	Status	Scale	Charm	Channel	Rev	Exposed	Message
os-glance	27.0.0	active	1	glance	2024.1/stable	621	no	Unit is ready
os-glance-mysql-router	8.0.42	active	1	mysql-router	8.0/stable	257	no	Unit is ready

Unit	Workload	Agent	Machine	Public address	Ports	Message
os-glance/0*	active	idle	0/lxd/6	10.210.121.236	9292/tcp	Unit is ready
os-glance-mysql-router/0*	active	idle		10.210.121.236		Unit is ready

Machine	State	Address	Inst id	Base	AZ	Message
0	started	10.210.121.100	manual:oswm-con-01	ubuntu@22.04		Manually provisioned machine
0/lxd/6	started	10.210.121.236	juju-42d5f2-0-lxd-6	ubuntu@22.04		Container started

Deploy Neutron

We will deploy `neutron-api` to LXD `0`, `neutron-gateway` to machine `0`, `neutron-openvswitch` to machine `1`, `2`

```
ubuntu@juju-controller:~$ juju deploy -n 1 --to lxd:0 --channel 2024.1/stable --config openstack-lab.yaml neutron-api os-neutron-api --constraints spaces=external,internal --bind "external admin=internal amqp=internal cluster=internal ha=internal internal=internal neutron-api=internal neutron-load-balancer=internal neutron-plugin-api=internal neutron-plugin-api-subordinate=internal public=external shared-db=internal"
Deployed "os-neutron-api" from charm-hub charm "neutron-api", revision 603 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy -n 1 --to 0 --channel 2024.1/stable --config openstack-lab.yaml neutron-gateway os-neutron-gateway --bind "external amqp=internal amqp-nova=internal cluster=internal data=overlay ha=internal neutron-plugin-api=internal"
Deployed "os-neutron-gateway" from charm-hub charm "neutron-gateway", revision 539 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy --channel 2024.1/stable --config openstack-lab.yaml neutron-openvswitch os-neutron-openvswitch --bind "external amqp=internal data=overlay neutron-control=internal neutron-plugin=internal neutron-plugin-api=internal"
Deployed "os-neutron-openvswitch" from charm-hub charm "neutron-openvswitch", revision 578 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy --channel 8.0/stable mysql-router os-neutron-api-mysql-router --bind "external shared-db=internal db-router=internal"
Deployed "os-neutron-api-mysql-router" from charm-hub charm "mysql-router", revision 257 in channel 8.0/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju relate os-neutron-gateway:amqp os-rabbitmq-server:amqp
ubuntu@juju-controller:~$ juju relate os-neutron-api os-neutron-openvswitch
ubuntu@juju-controller:~$ juju relate os-neutron-openvswitch os-rabbitmq-server
ubuntu@juju-controller:~$ juju relate os-keystone:identity-service os-neutron-api:identity-service
ubuntu@juju-controller:~$ juju relate os-neutron-api-mysql-router:db-router os-mysql-innodb-clusters:db-router
ubuntu@juju-controller:~$ juju relate os-neutron-api-mysql-router:shared-db os-neutron-api:shared-db
ubuntu@juju-controller:~$ juju relate os-rabbitmq-server:amqp os-neutron-api:amqp
```

Deploy Nova

- Deploy Nova Cloud Controller

```
ubuntu@juju-controller:~$ juju deploy -n 1 --to lxd:0 --channel 2024.1/stable --config openstack-lab.yaml nova-cloud-controller os-nova-cloud-controller --constraints spaces=external,internal --bind "external admin=internal amqp=internal amqp-cell=internal cinder-volume-service=internal cloud-compute=internal cloud-controller=internal cluster=internal dashboard=internal ha=internal identity-service=internal image-service=internal internal=internal memcache=internal neutron-api=internal nova-cell-api=internal placement=internal shared-db-cell=internal shared-db=internal"
Deployed "os-nova-cloud-controller" from charm-hub charm "nova-cloud-controller", revision 782 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy --channel 8.0/stable mysql-router os-ncc-mysql-router --bind "external shared-db=internal db-router=internal"
Deployed "os-ncc-mysql-router" from charm-hub charm "mysql-router", revision 257 in channel 8.0/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju relate os-ncc-mysql-router:db-router os-mysql-innodb-clusters:db-router
ubuntu@juju-controller:~$ juju relate os-ncc-mysql-router:shared-db os-nova-cloud-controller:shared-db
ubuntu@juju-controller:~$ juju relate os-nova-cloud-controller:identity-service os-keystone:identity-service
ubuntu@juju-controller:~$ juju relate os-nova-cloud-controller:amqp os-rabbitmq-server:amqp
ubuntu@juju-controller:~$ juju relate os-nova-cloud-controller:neutron-api os-neutron-api:neutron-api
ubuntu@juju-controller:~$ juju relate os-glance:image-service os-nova-cloud-controller:image-service
```

Deploy Nova

- Deploy Nova Compute

```
ubuntu@juju-controller:~$ juju deploy -n 2 --to 1,2 --channel 2024.1/stable --config openstack-lab.yaml nova-compute os-nova-compute --bind "external  
amqp=internal ceph=storage ceph-access=storage cloud-compute=internal cloud-credentials=internal compute-peer=internal internal=internal ephemeral-  
backend=internal image-service=internal neutron-plugin=internal secrets-storage=internal"  
Deployed "os-nova-compute" from charm-hub charm "nova-compute", revision 771 in channel 2024.1/stable on ubuntu@22.04/stable
```

```
ubuntu@juju-controller:~$ juju relate os-nova-compute:image-service os-glance:image-service  
ubuntu@juju-controller:~$ juju relate os-nova-compute:amqp os-rabbitmq-server:amqp  
ubuntu@juju-controller:~$ juju relate os-ceph-mon:client os-nova-compute:ceph  
ubuntu@juju-controller:~$ juju relate os-neutron-openvswitch os-nova-compute  
ubuntu@juju-controller:~$ juju relate os-nova-cloud-controller:cloud-compute os-nova-compute:cloud-compute
```

Deploy Placement

We will deploy `placement` to LXD `0`

```
ubuntu@juju-controller:~$ juju deploy -n 1 --to lxd:0 --channel 2024.1/stable --config openstack-lab.yaml ch:placement os-placement --constraints spaces=external,internal --bind "external admin=internal amqp=internal cluster=internal ha=internal identity-service=internal internal=internal placement=internal shared-db=internal"
Deployed "os-placement" from charm-hub charm "placement", revision 102 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy --channel 8.0/stable mysql-router os-placement-mysql-router --bind "external shared-db=internal db-router=internal"
Deployed "os-placement-mysql-router" from charm-hub charm "mysql-router", revision 257 in channel 8.0/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju relate os-placement-mysql-router:db-router os-mysql-innodb-clusters:db-router
ubuntu@juju-controller:~$ juju relate os-placement-mysql-router:shared-db os-placement:shared-db
ubuntu@juju-controller:~$ juju relate os-placement:identity-service os-keystone:identity-service
ubuntu@juju-controller:~$ juju relate os-placement os-rabbitmq-server
ubuntu@juju-controller:~$ juju relate os-placement:placement os-nova-cloud-controller:placement
```

Deploy Cinder

```
ubuntu@oscwm-con-01:~$ ubuntu@juju-controller:~$ juju deploy -n 1 --to lxd:0 --channel 2024.1/stable --config openstack-lab.yaml ch:cinder os-cinder --constraints spaces=external,internal --bind "external admin=internal amqp=internal backup-backend=internal ceph=storage cinder-volume-service=internal cluster=internal ha=internal identity-service=internal internal=internal shared-db=internal storage-backend=storage"
Deployed "os-cinder" from charm-hub charm "cinder", revision 690 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy --channel 8.0/stable mysql-router os-cinder-mysql-router --bind "external shared-db=internal db-router=internal"
Deployed "os-cinder-mysql-router" from charm-hub charm "mysql-router", revision 257 in channel 8.0/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju relate os-cinder-mysql-router:db-router os-mysql-innodb-clusters:db-router
ubuntu@juju-controller:~$ juju relate os-cinder-mysql-router:shared-db os-cinder:shared-db
ubuntu@juju-controller:~$ juju relate os-cinder:cinder-volume-service os-nova-cloud-controller:cinder-volume-service
ubuntu@juju-controller:~$ juju relate os-cinder:identity-service os-keystone:identity-service
ubuntu@juju-controller:~$ juju relate os-cinder:amqp os-rabbitmq-server:amqp
ubuntu@juju-controller:~$ juju relate os-cinder:image-service os-glance:image-service
```

Deploy Cinder

```
ubuntu@juju-controller:~$ juju deploy --channel 2024.1/stable --config openstack-lab.yaml ch:cinder-ceph os-cinder-ceph
Deployed "os-cinder-ceph" from charm-hub charm "cinder-ceph", revision 533 in channel 2024.1/stable on ubuntu@22.04/stable
```

```
ubuntu@juju-controller:~$ juju relate os-cinder-ceph:storage-backend os-cinder:storage-backend
```

```
ubuntu@juju-controller:~$ juju relate os-cinder-ceph:ceph os-ceph-mon:client
```

```
ubuntu@juju-controller:~$ juju relate os-cinder-ceph:ceph-access os-nova-compute:ceph-access
```

```
ubuntu@juju-controller:~$ juju deploy cinder-backup --channel 2024.1/stable os-cinder-backup
```

```
Deployed "os-cinder-backup" from charm-hub charm "cinder-backup", revision 81 in channel 2024.1/stable on ubuntu@22.04/stable
```

```
ubuntu@juju-controller:~$ juju relate os-cinder-backup:backup-backend os-cinder:backup-backend
```

```
ubuntu@juju-controller:~$ juju relate os-cinder-backup:ceph os-ceph-mon:client
```

Deploy Horizon

```
ubuntu@juju-controller:~$ juju deploy -n 1 --to lxd:0 --channel 2024.1/stable --config openstack-lab.yaml openstack-dashboard os-openstack-dashboard --constraints spaces=external,internal --bind "external application-dashboard=external cluster=internal dashboard=internal dashboard-plugin=internal identity-service=internal shared-db=internal website=external"
Deployed "os-openstack-dashboard" from charm-hub charm "openstack-dashboard", revision 691 in channel 2024.1/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju deploy --channel 8.0/stable mysql-router os-dashboard-mysql-router --bind "external shared-db=internal db-router=internal"
Deployed "os-dashboard-mysql-router" from charm-hub charm "mysql-router", revision 257 in channel 8.0/stable on ubuntu@22.04/stable

ubuntu@juju-controller:~$ juju relate os-dashboard-mysql-router:db-router os-mysql-innodb-clusters:db-router
ubuntu@juju-controller:~$ juju relate os-dashboard-mysql-router:shared-db os-openstack-dashboard:shared-db
ubuntu@juju-controller:~$ juju relate os-openstack-dashboard:identity-service os-keystone:identity-service
```

Post Deployment

```
openstack image create --public --disk-format qcow2 --container-format bare --file ~/images/cirros-0.6.2-x86_64-disk.img "Cirros 0.6.2"

openstack aggregate create --zone AZ_Private01_DC1 Private01_DC1
openstack compute service list --service nova-compute -c Host --noindent -f value | xargs -I{} openstack aggregate add host Private01_DC1 {}

openstack flavor create --ram 128 --disk 1 --vcpus 1 --public GP.1C128M
openstack flavor create --ram 1024 --disk 20 --vcpus 1 --public GP.1C1G

openstack network create --availability-zone-hint AZ_Private01_DC1 --share --enable --mtu 1500 --external --default --provider-network-type vlan --provider-physical-network physnet1 --provider-segment 31 Subnet_Private01_DC1

openstack subnet create --dhcp --gateway 10.210.131.1 --network 10.210.131.0/24 --ip-version 4 --network Subnet_Private01_DC1 --allocation-pool start=10.210.131.20,end=10.210.131.200 --dns-nameserver 8.8.8.8 --dns-nameserver 8.8.4.4 --dns-nameserver 1.1.1.1 --subnet-range 10.210.131.0/24 Subnet_Private01_DC1


openstack security group create admin-allow-all
openstack security group rule create --remote-ip 0.0.0.0/0 --protocol any admin-allow-all

openstack keypair create --public-key resource/publikkey.pub mine

openstack volume type create ceph-ssd --property volume_backend_name=ceph-ssd

openstack server create --security-group admin-allow-all --key-name mine --flavor GP.1C1G --image "Cirros 0.6.2" --network Subnet_Private01_DC1 --availability-zone AZ_Private01_DC1 "cirros-test111"
```

THANK YOU



EasyStack
open cloud computing



datacomm

flexi

WOWRACK



ZConverter Cloud



**SIVALI
CLOUD
TECHNOLOGY**

boer
technology

NASHTAGROUP
TECHNOLOGY AND SERVICES COMPANY

nevacloud

Yogyakarta, 19 July 2025